# Polymeric Sands & Dust



## Gator G2 High Performance Sand

- \* Can be used for joints up to a maximum of 2"
- \* Use on Concrete Pavers, Wetcast & Natural Stone
- \* Not recommended for Concrete Overlay









Beige Slate Gray Ivory Black

#### Gator G2 Maxx Sand

- \* Can be used for joints up to a maximum of 4"
- \* Use on Concrete Pavers, Wetcast & Natural Stone
- \* Ideal for : Overlays, Pool Soundings & Sloping areas







e Slate Gray

Ivory

#### **Gator Dust**

- \* Can be used for joints 1/2" to 4"
- \* Use on Natural Stone
- \* **Do Not** use on Concrete Pavers





Gray Beige



## **NextGel** Polymeric Jointing Sand

- \* Can be used for joints up to a maximum of 4"
- \* Use on Concrete Pavers & Natural Stone
- \* For Heavy-traffic and high-humidity areas, steep slopes, large commercial parking lots and false and wide joints



# NOCO "No Compaction"

\* Polymeric joint specially developed for the installation of flagstones and other paving materials for which mechanical compaction is not possible or difficult.



# **EASY**Joint

- \* All Weather Paving Joint Compound
- \* Permeable (flow rate between 50-70 ins per hour)
- \* Wet sweep in compound
- \* 28 lbs. Tubs



Mushroom



**Stone Grey**